

Objective

ELLA wall luminaries offer a versatile lighting solution with both mono and bidirectional options, making them suitable for a wide range of applications, complemented by their sophisticated Italian design. The utilization of high-efficiency LED technology ensures not only elegance but also dependable performance and energy savings. ELLA stands out as a refined lighting choice for wall illumination, boasting an elegant design and the flexibility to choose the direction of light. Our extensive experience in producing this light over the years has been driven by the increasing demand from designers seeking a variety of options.

Obiettivo

Le appliques murali ELLA offrono una soluzione illuminante versatile con opzioni sia monocromatiche che bidirezionali, rendendole adatte a una vasta gamma di applicazioni, valorizzate dal loro sofisticato design italiano. L'utilizzo della tecnologia LED ad alta efficienza garantisce non solo eleganza, ma anche prestazioni affidabili e risparmio energetico. ELLA si distingue come una scelta illuminante raffinata per l'illuminazione delle pareti, vantando un design elegante e la flessibilità di scegliere la direzione della luce. La nostra vasta esperienza nella produzione di questa luce nel corso degli anni è stata guidata dalla crescente richiesta da parte dei designer alla ricerca di una varietà di opzioni.

Description

Housing - Made of die cast aluminum powder coated with choice of RAL color

Diffuser - Frosted tempered glass diffuser specially for LED

Reflector - Anodized aluminum reflector



LED - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.

Standards - manufactured in accordance with tested as per PTPS IEC 62722

CODE	WATTAGE	LUMEN	SIZE mm
1612812	2X6W	1320lm	95 X 65 X 155 H
1612816	2X8W	1760lm	95 X 65 X 155 H



LED	ENERGY STAR	ECO
PHASE DIMMING	DALI	1-10 DIMMING
55°C	Glowing Wire Test - 850°	-25°C
IP 65	IK 08	UGR <21
SDCM 2.0/3.0	COMPLIANCE	LM-79 TM-21
CIDET	EAC	LM-80
PASEL ACCREDITATION	COB	CRI >90
SELV	F	series wiring
ROHS	CE	COMPLIANCE
U	185-265V	50/60Hz
A++		



2700K
3000K
4000K
5000K
6000K
6500K

LED Drivers - PHILIPS GTCI TRIDONIC LED Chips - BRIDGELUX CREE SHARP SAMSUNG PHILIPS CITIZEN

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.