

Objective

All the Dyana family wears the signature of quality and beauty of a regnant in the spotlights world. Available in a choice of options in a matter of design and power, plus the chance to more than easily replace the LED source with another one, same or different it will be. This item is pure functionality and adaptable to every requirement. The high efficiency of the LED source ensures excellent performances and low consumptions. Energy and economy savings are a little advantage compared to the design of this item, which makes technicians and artists in love with it.

Obiettivo

Tutta la famiglia Dyana porta la firma della qualità ed eleganza di un regnante nel mondo dei faretti da incasso. Disponibile in una scelta di opzioni per quanto concerne il design e la potenza, più l'opportunità di sostituire più che facilmente la sorgente LED con un'altra, sia essa uguale o differente. Questo articolo è pura funzionalità ed adattabile per ogni esigenza. La sorgente LED ad alta efficienza assicura eccellenti performance e bassi consumi. Risparmio energetico ed economico sono niente più che un piccolo vantaggio se comparati al design di questo prodotto, che si fa amare sia dai tecnici che dagli artisti.

Description

Housing - Die cast aluminum powder coated with choice of RAL colors


Diffuser - Tempered clear glass with optical lens.

Reflector - Anti glare ring reflector.








LED - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.



Standards - manufactured in accordance with tested as per PTPS IEC 62722



Color - White, Satin, Silver, Gold, Black

CODE	WATTAGE	LUMEN	SIZE mm	
6092010	10W	1200lm	Ø80 X 87mm	Ø75mm
6092013	13W	1560lm	Ø100 X 94mm	Ø90mm



		
PHASE DIMMING	DALI	1-10 DIMMING
55°C	Glowing Wire Test - 850°	
-25°C		
IP 44	ECO	UGR <19
		SDCM 2.0/3.0
	EAC	COMPLIANCE
		LM-78 TM-21
PASEL ACCREDITATION	COB	CRI >90
	SELV	series wiring
CE		
A++	85~265V 50/60Hz	



	2700K	
	3000K	
	4000K	
	5000K	
	6000K	
	6500K	

LED Drivers - PHILIPS    TRIDONIC | LED Chips - BRIDGELUX    PHILIPS 

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.