

**Objective**

Different designs with IP 54 rating for a little recessed spotlights available in 6 or 13 watt power. The emitted light is bright, homogeneous and comfortable, the application are many. Equipped with high technology LED light source, Waterino promises consistent energy savings and a long work life span. The lighting result are guaranteed for all the life of the product. The family is divided in two different lines because of the different IP range: one line is suitable for indoor applications, the second one is perfect even in outdoor locations (great choice above the mirror in the bathroom, sauna, Jacuzzi).

**Obiettivo**

Diversi modelli con grado di protezione IP 54 per piccoli faretti da incasso disponibili con potenza da 6 o 13 watt. La luce emessa è brillante, omogenea e confortevole, gli utilizzi possibili sono svariati. Equipaggiato con sorgente LED ad alta tecnologia, Waterino promette consistente risparmio energetico e una lunga vita di funzionamento. I risultati illuminotecnici sono garantiti per l'intera vita del prodotto. La famiglia è suddivisa in due linee differenti a cause del diverso valore IP: una linea è adatta per essere applicata in ambienti interni, la seconda è perfetta anche in luoghi all'aperto (scelta eccellente al di sopra dello specchio del bagno, in sauna, in Jacuzzi).

**Description**

**Housing** - Die cast aluminium powder coated with choice of RAL colors

**Diffuser** - Clear tempered glass.

**Reflector** - Pure anodized aluminum reflector.




**LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.

**Standards** - manufactured in accordance with tested as per PTPS IEC 62722, EN 60598-1

CODE	WATTAGE	LUMEN	SIZE mm	
6074206	6W	720lm	Ø90 X 52 H	Ø80
6074213	13W	1560lm	Ø90 X 96 H	Ø80



PHASE DIMMING	DALI	1-10 DIMMING	
55°C	Glowing Wire Test - 850°		
-25°C	Adjusting		
IP 54	UGR <19	SDCM 2.0/3.0	
	EAC	COMPLIANCE LM-79 TM-21 (lm-80)	
PASEL ACCREDITATION	COB	CRI >90	
	SELV		series wiring
CE			U
<b>A++</b>	85~265V 50/60Hz		



- 2700K
- 3000K
- 4000K
- 5000K
- 6000K
- 6500K



LED Drivers - PHILIPS TRIDONIC | LED Chips - BRIDGELUX PHILIPS

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that has recent technology will not alter the function of the product. Specification sheets found at [www.romaluce.it](http://www.romaluce.it) are the most recent versions and supercede all other printed or electronic versions.