

Objective

Extractable, adjustable, recessed luminaire for neutral white LED lamp. Passive heat dispatch system. Die-cast aluminium main body and frame; stainless steel rotation ring. Rotation ring with safety cover in a high resistance thermoplastic material. Body adjusted with a manual manoeuvre device: internal 15° - external 60° - rotation on 350° axis. Reflector with high efficiency super pure aluminium optic - spot beam angle. Die-cast aluminium lamp body closure ring. Tempered transparent glass screen. Electronic control gear supplied and connected to the luminaire.

Obiettivo

Apparecchio da incasso estraibile, orientabile e orientabile per lampada a LED bianco neutro. Sistema di trasmissione del calore passivo. Main in alluminio pressofuso corpo e telaio; ghiera di rotazione in acciaio inossidabile. Anello di rotazione con copertura di sicurezza in materiale termoplastico ad alta resistenza. Corpo regolato con un dispositivo di manovra manuale: interno 15° - esterno 60° - rotazione su asse 355°. Riflettore con ottica in alluminio super puro ad alta efficienza - angolo del fascio spot. Anello di chiusura corpo lampada in alluminio pressofuso. Schermo in vetro trasparente temperato. Elettronico alimentatore fornito e collegato all'apparecchio di illuminazione.

Description

Housing - Die cast aluminium powder coated with choice of RAL colors


Diffuser - Polycarbonate PMMA or tempered glass diffuser.

Reflector - Pure aluminum finish reflector with option of multi electro plating.















LED - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.





Standards - manufactured in accordance with tested as per PTPS IEC 62722

Accessories - Honeycomb

CODE	WATTAGE	LUMEN	SIZE mm	
5080210	10W	1250lm	Ø96 X 68H	Ø85
5080215	15W	1875lm	Ø145 X 130H	Ø120
5080220	20W	2500lm	Ø145 X 130H	Ø120
5080230	30W	3750lm	Ø180 X 170H	Ø165
5080235	35W	4375lm	Ø180 X 170H	Ø165



			
PHASE DIMMING	DALI	1-10 DIMMING	
55°C	Glowing Wire Test - 850°		
-25°C	Adjustable		
IP 44	UGR <19	SDCM 2.0/3.0	
		COMPLIANCE LM-79 TM-21 (lm-80)	
PASEL ACCREDITATION	COB	CRI >90	
	SELV		series wiring
			
A++	85~265V 50/60Hz		



2700K
3000K
4000K
5000K
6000K
6500K



LED Drivers - PHILIPS    TRIDONIC  BRIDGELUX    PHILIPS  Micro HumanTech

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.