

Objective

The luminaries luminous flux and the luminaries connected wattage quoted in the table may change as a result of technical progress. This is new revolution of design allow designers to have the light demanded for ramp & pedestrian wall light. Even If they don't have groove on wall the Amalfi gives none groove solution to engineers.

Obiettivo

Il flusso luminoso dei luminari e i wattaggi collegati indicati nella tabella possono variare a seguito del progresso tecnico. Questa nuova rivoluzione del design consente ai progettisti di avere la luce richiesta per applique da rampa e pedonali. Anche se non hanno scanalature sul muro, Amalfi non offre alcuna soluzione di scanalatura agli ingegneri.

Description

- Housing** - Pure die cast aluminum body in anodized or powder coating finishes.
- Diffuser** - Clear tempered glass diffuser.
- LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.
- Standards** - manufactured in accordance with tested as per PTPS IEC 62722
- Colors** - Titanium anodized, Silver anodized, Black powder coated
White powder coated.

CODE	WATTAGE	LUMEN	SIZE mm
1623804	4W	420lm	Ø100 X 30 H
1623808	8W	840lm	Ø215 X 36 H



PHASE DIMMING

55°C

-25°C

IP 65

IK 06

UGR <21

SDCM 2.0/3.0

PASEL ACCREDITATION

SMD

CRI >90

SELV

CE

A++

LED

ECO



Glowing Wire Test - 850°

COMPLIANCE

LM-79 TM-21

series wiring

185-265V 50/60Hz



60°

2700K

3000K

4000K

5000K

6000K

6500K

LED Drivers - PHILIPS **GTI** **MEAN WELL** **GTCL TRIDONIC** LED Chips - BRIDGELUX **CREE** **SHARP** **SAMSUNG** **PHILIPS** **CITIZEN**

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.