

Objective

Locanda Family has many different models, but they all have one thing in common: its quite small tubular shape or round circle shape is what defines this range of lighting fixtures. Whether in single-use or accompanied by another cylinder or decorative light to make it directional lighting effect or reading light flux, this one is always a beauty. As a surface mounted or Simi recessed on the wall for some range of the family Locanda comes in many playful finishing colors. To complete the range, also wall-mounted versions are available high-efficiency low consumption of power applicable to modification of details to match customer requirements.

Obiettivo

La famiglia Locanda è costituita di molti modelli differenti, ma tutti sono accomunati da una caratteristica che ne definisce la gamma: la forma, tubolare o circolare che sia, è di dimensioni sensibilmente ridotte. Questa peculiarità definisce la bellezza ed eleganza dell'effetto di luce risultante, assicurando un risultato perfetto nell'utilizzo della luminaria tanto come solista, quanto accompagnata da una qualunque altra luminaria a scopo prettamente architetturelle o decorativo. Gli articoli di categoria montati a superficie o ad incasso, sono disponibili in svariati colori di rifinitura. A completare il pacchetto, la reperibilità degli apparecchi ad alta efficienza e basso consumo energetico anche con dettagli personalizzabili mirati a soddisfare qualunque esigenza del cliente.


Description

Housing - Made of die cast aluminum powder coated with choice of RAL color

















Diffuser - PMMA optical lens specially for LED



LED - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.

Standards - manufactured in accordance with tested as per PTPS IEC 62722

CODE	WATTAGE	LUMEN	SIZE mm	
9400701	1W	104lm	Ø95 X 77.5H	Ø69



			
55°C	Glowing Wire Test - 850°		
-25°C	IP 44	IK 06	UGR <19
			SDCM 2.0/3.0
		COMPLIANCE	
			
	COB	CRI >90	
	SELV		series wiring
			
	85-265V 50/60Hz		



2700K
3000K
4000K
5000K



LED Drivers - PHILIPS    TRIDONIC | LED Chips - BRIDGELUX    PHILIPS 

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.