

Objective

Ideal choices of size and design, this range is suitable for every wall. The high quality of the raw materials ensures high resistance to dust, extraneous corps in general, humidity and water. The LED system is highly efficient to provide excellent luminous flux results in low consumptions. The item presents also features as easy installation and low maintenance requirements.

Obiettivo

Scelte ideali di dimensioni e design, questa gamma è adatta a ogni parete. L'alta qualità delle materie prime garantisce un'elevata resistenza a polvere, corpi estranei in genere, umidità e acqua. Il sistema LED è altamente efficiente per fornire un flusso luminoso eccellente con bassi consumi. L'articolo presenta anche caratteristiche quali facilità di installazione e scarsa necessità manutenzione.



Description

- Housing** - Die cast aluminium powder coated with choice of RAL colors
- Diffuser** - Tempered glass diffuser or PMMA optical lens.
- Reflector** - White laminated aluminum reflector.
- LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.
- Standards** - manufactured in accordance with tested as per PTPS IEC 62722
- Accessories** - PVC back box.

CODE	WATTAGE	LUMEN	SIZE mm	
1514110	7W	735lm	Ø135 X 90H	Ø129 X 100



PHASE DIMMING		LED	ECO
55°C	Glowing Wire Test - 850°	-25°C	
IP 65	IK 08	UGR <19	SDCM 2.0/3.0
	EAC	COMPLIANCE LM-79 TM-21	
PASEL ACCREDITATION	SMD	CRI >90	
	SELV		series wiring
CE			U
A++	220~240V 50/60Hz		



- 2700K
- 3000K
- 4000K
- 5000K
- 6000K
- 6500K



LED Drivers - PHILIPS TRIDONIC | LED Chips - BRIDGELUX PHILIPS

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.