

**Objective**

Clean profiles, coated in matt colour, defined lines and important diameter are the promise that this projector will be noticed. The LED technology here mounted ensures the quantity and the quality of the lumen output: le luminaire emits pure, homogeneous and uniform light. Distinguished for its essential design, the Tracitly projector is clearly studied for retail projects. This projectors applied on 2 phase, 3 wires rail connected to high voltage which gives freedom of projectors mounted into one single rail.

**Obiettivo**

Profili puliti, rivestimento in colore opaco, linee definite e diametro importante sono la promessa che questo proiettore verrà notato. La tecnologia LED qui montata garantisce la quantità e la qualità dell'emissione del lume: le apparecchio emette luce pura, omogenea e uniforme. Distinto per il suo design essenziale, il proiettore Tracitly è chiaramente studiato per progetti di vendita al dettaglio. Questi proiettori sono applicati su binari a 2 fili e 3 fili collegati all'alta tensione che offre libertà ai proiettori montati su un unico binario.

**Description**

- Housing** - Die cast aluminium body with variety of RAL finishes.
- Diffuser** - Tempered glass or polycarbonate clear diffuser with optical lens.
- Reflector** - Anodized aluminium reflector.
- Adaptor** - Made of thermoplastic
- LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.
- Standards** - manufactured in accordance with EN 60598-1 and 60598-2-1

CODE	WATTAGE	LUMEN	SIZE mm
9100208	08W	960lm	Ø69 X123 X 150 H
9100212	12W	1440lm	Ø69 X123 X 150 H
9100215	15W	1800lm	Ø69 X123 X 150 H
9100220	20W	2400lm	Ø90 X150 X 190 H
9100225	25W	3000lm	Ø90 X150 X 190 H
9100230	30W	3600lm	Ø90 X150 X 190 H
9100235	35W	4200lm	Ø90 X150 X 190 H
9100240	40W	4800lm	Ø100 X170 X 200 H
9100245	45W	5400lm	Ø100 X170 X 200 H



LED

PHASE DIMMING DALI

ECO

55°C  
-25°C

Glowing Wire Test - 850°

IP 44

Adjustable

UGR <19

SDCM 2.0/3.0

CIDET

EAC

COMPLIANCE

LM-79 TM-21

LM-80

PASEL ACCREDITATION

COB

CRI >90

ROHS

SELV

F

ENERGY STAR




CE

COMPLIANCE

U

**A++**

85~265V  
50/60Hz



- 2700K
- 3000K
- 4000K
- 5000K
- 6000K
- 6500K



LED Drivers - PHILIPS GTI | MEAN WELL | GTCI TRIDONIC | LED Chips - BRIDGELUX | CREE | SHARP | SAMSUNG | PHILIPS | CITIZEN

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at [www.romaluce.it](http://www.romaluce.it) are the most recent versions and supercede all other printed or electronic versions.