

**Objective**

New innovative design for wall led luminaries with indirect lighting reflection give totally new feeling of outdoor lighting application weather proof protection rated ip54 can give freedom to use as many area has wet and medium humidity.

**Obiettivo**

Il nuovo design innovativo per apparecchi di illuminazione a parete con riflesso indiretto dell'illuminazione offre una sensazione completamente nuova di applicazione di illuminazione per esterni La protezione a prova di intemperie con grado di protezione IP54 può dare la libertà di utilizzo poiché molte aree presentano umidità umida e media.

**Description**

**Housing** - Pure die cast aluminum body in anodized or powder coating finishes.

**Diffuser** - Opal polycarbonate diffuser.


**LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.

**Standards** - manufactured in accordance with tested as per PTPS IEC 62722


**Colors** - Titanium anodized, Silver anodized, Black powder coated

White powder coated.

CODE	WATTAGE	LUMEN	SIZE mm
1621214	2 X 7W	1330lm	125 X 41 X 250 H



LED	ENERGY STAR	ECO
55°C	Glowing Wire	
-25°C	Test - 850°	
IP 65	IK 07	UGR <21
		SDCM 2.0/3.0
CIDET	EAC	COMPLIANCE
		LM-79 TM-21 (lm-80)
PASEL ACCREDITATION	SMD	CRI >90
ROHS	SELV	F series wiring
CE	COMPLIANCE	U
A++	185-265V	50/60Hz



- 2700K
- 3000K
- 4000K
- 5000K
- 6000K
- 6500K



LED Drivers - PHILIPS GHI MWM GTCI TRIDONIC LED Chips - BRIDGELUX CREE SHARP SAMSUNG PHILIPS CITIZEN

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will alter the function of the product. Specification sheets found at [www.romaluce.it](http://www.romaluce.it) are the most recent versions and supercede all other printed or electronic versions.