

## Objective

C-Donge range of products is thought to provide a luminaire series with high quality and very professional design signature. The feature of this item is its emitted light, which is coming both from the centre and from the around corner, providing as focus beam characterized by high efficiency lumen output, as surround marker effect. The aluminium body and heat sink ensure high performance in a matter of quality, safety, and durability. Practical, versatile, suitable to be used in a wealth of applications thanks to its unrivalled design flexibility, it is particularly indicated to illuminate shop windows and retail spaces, private home rooms or hotel rooms.

## Obiettivo

La gamma di prodotti C-Donge è pensata per dare vita ad una serie di luminarie firmate da alta qualità e dal design professionale. La peculiarità di questo articolo è data dalla luce emessa, che proviene sia dal centro che dalla corona che lo circonda, dando tanto un angolo di luce focalizzato caratterizzato dall'alta efficienza in lumen, tanto un effetto di marcatura attorno. Il corpo ed il dissipatore in alluminio assicurano ottime performance in termini di qualità, sicurezza e durevolezza. Pratico, versatile, adatto per una moltitudine di impieghi grazie alla sua flessibilità di design senza rivali, è particolarmente indicato per illuminare le vetrine dei negozi e gli spazi commerciali, le stanze di una casa privata o di un albergo.

## Description

**Housing** - Die cast aluminium with PVC coated with choice of RAL colors


**Diffuser** - Clear tempered glass lamp diffuser.

**Reflector** - Pure anodized aluminum reflector.












**LED** - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.




**Standards** - manufactured in accordance with tested as per PTPS IEC 62722, EN 60598-1

**Color** - White, Satin, Silver, Black,Gold

CODE	WATTAGE	LUMEN	SIZE mm	
6091506	6W	720lm	80 X 80 X 52 H	Ø67
6091509	9W	1080lm	80 X 80 X 52 H	Ø67
6091512	12W	1440lm	112 X 112 X 68 H	Ø95
6091515	15W	1800lm	112 X 112 X 68 H	Ø95
6091520	20W	2400lm	145 X 145 X 77 H	Ø135



			
PHASE DIMMING	DALI	1-10 DIMMING	
55°C	Glowing Wire Test - 850°		
-25°C	Adjusting		
IP 44	UGR <19	SDCM 2.0/3.0	
	EAC	COMPLIANCE LM-79 TM-21 LM-80	
PASEL ACCREDITATION	COB	CRI >90	
	SELV		series wiring
CE			U
<b>A++</b>	85-265V 50/60Hz		



TRIO  
2700K  
3000K  
4000K  
5000K  
6000K  
6500K



LED Drivers - PHILIPS    TRIDONIC  BRIDGELUX  SHARP  PHILIPS  Micro HumanTech

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that has recent technology will not alter the function of the product. Specification sheets found at [www.romaluce.it](http://www.romaluce.it) are the most recent versions and supercede all other printed or electronic versions.