

Objective

The linear light ideal to make all your facades very fashion and bright. The LED source, warranting high performances in lumen rates and light quality, saves considerable energy, so the item has "green" features. As light quality we mean uniform, bright and warm light, which has to be also comfortable and pleasant, respecting the human eye needs: all this is possible thanks to the low glare rating provided in this item. The long working lifespan is guaranteed from the quality of LED and the raw materials.

Obiettivo

L'apparecchio di illuminazione lineare ideale per rendere tutte le tue facciate molto fashion e luminose. La sorgente LED, che garantisce elevate prestazioni in termini di luminosità e qualità della luce, consente di risparmiare energia considerevole, pertanto l'articolo ha caratteristiche "verdi". Come luce, intendiamo luce uniforme, luminosa e calda, che deve essere anche confortevole e piacevole, nel rispetto delle esigenze dell'occhio umano: tutto ciò è possibile grazie al basso livello di abbagliamento fornito in questo articolo. La durata della vita lavorativa è garantita dalla qualità dei LED e delle materie prime.

Description

Housing - Extruded aluminium casting profile powder coated with choice of RAL colors.

Diffuser - Tempered clear glass with optical glass lens.

LED - reducing energy consumption with L80/B10/F10 50,000 hrs lifetime.

Standards - manufactured in accordance with tested as per PTPS IEC 62722.

Accessories - Honeycomb, mounting brackets.

CODE	WATTAGE	LUMEN	SIZE mm
2147210	10W	1180lm	500 X 50X 76H
2147212	12W	1416lm	1000 X 50X 76H
2147220	20W	2360lm	1000 X 50X 76H
2147225	25W	2950lm	1000 X 50X 76H
2147240	40W	4720lm	1000 X 50X 76H



LED	ENERGY STAR	ECO	DIFFERENT LENGTH
PHASE DIMMING	DALI	1-10 DIMMING	
65°C	Glowing Wire Test - 850°		
-20°C			
IP 66	IK 09	UGR <21	SDCM 2.0/3.0
CIDET	EAC	COMPLIANCE LM-79 TM-21 LM-80	
PASEL ACCREDITATION	SMD	CRI >90	
SELV	ROHS	F	series wiring
CE	COMPLIANCE	U	
A++			DC 24V

Honeycomb Bracket

5° 12° 20° 30°
60° 15X30° 10X60°

RGB
2700K
3000K
4000K
5000K
6000K

LED Drivers - PHILIPS GTCI TRIDONIC LED Chips - BRIDGELUX CREE SHARP SAMSUNG PHILIPS CITIZEN

In a continuing effort to offer the best product possible, we reserve the right to change, without notice, specifications or materials that in our opinion will not alter the function of the product. Specification sheets found at www.romaluce.it are the most recent versions and supercede all other printed or electronic versions.